

VALVE DATA SHEET

| Item # | Size | Class | Quantity | <h2 style="margin: 0;">Ball Valve</h2> |
|----------------|--------|--------|----------|--|
| 9 | 2 inch | 600 | 1 | |
| Manufacturer : | | Dafram | | |

Design Data :

| | |
|-----------------|--|
| Type and Design | Design API 6D Pressure & Temperature Rating ASME B16.34 Flange Dims ASME B16.5 Trunnion |
| End Connection | RF Flanged |
| Operated | Lever |
| Model | |
| | |

Material Specification :

| | |
|-------|---------|
| Body | A105 |
| Ball | 316 SS |
| Seat | Nylon |
| Stem | 316 SS |
| Bolts | A193 B7 |
| Nuts | A194 2H |
| | |

Others :

| | |
|----------------------|----------------------|
| Test & Inspection | API 6D |
| Operating Parameters | |
| Max Diff. Pressure | Max Pressure |
| Temp. Range | -20° to 200 °C |
| Painting | Manufacture Standard |
| Applicable Standard | API 6D |
| | |

Certificate :

| | |
|----------------------|----------------------|
| Material Certificate | Mill Certificate 3.1 |
| | |
| | |

Remarks :

| |
|--|
| |
| |
| |

