

VALVE DATA SHEET

| Item # | Size | Class | Quantity | <h2 style="margin: 0;">Ball Valve</h2> |
|---------------------------------|--------|--------------------------------------------------------------------------------------------------|----------|----------------------------------------|
| 23 | 4 inch | 600 | 2 | |
| Manufacturer : | | LCM | | |
| Design Data : | | | | |
| Type and Design | | Design API 6D Pressure & Temperature Rating ASME B16.34 Flange Dims ASME B16.5 Trunnion | | |
| End Connection | | RF Flanged | | |
| Operated | | Gear | | |
| Model | | | | |
| Material Specification : | | | | |
| Body | | A350 LF2/ A105 | | |
| Ball | | CS+ENP | | |
| Seat | | Devlon | | |
| Stem | | 316 SS | | |
| Bolts | | A193 B7 | | |
| Nuts | | A194 2H | | |
| Others : | | | | |
| Test & Inspection | | API 6D | | |
| Operating Parameters | | | | |
| Max Diff. Pressure | | Max Pressure | | |
| Temp. Range | | -20° to 200 °C | | |
| Painting | | Manufacture Standard | | |
| Applicable Standard | | API 6D | | |
| Certificate : | | | | |
| Material Certificate | | Mill Certificate 3.1 | | |
| | | | | |
| | | | | |
| Remarks : | | | | |
| | | | | |
| | | | | |
| | | | | |